

Years PE Prepainted Steel Sheet Limited Warranty

LONGFA warrants that PE type Prepainted hot dipped steel sheet that made from prime quality with top paint thickness 20µm for use as application below , if erected within South Africa,will perform for five(5) years prior to perforation from the date of painting when exposed to normal atmospheric conditions subject to the following provisions:

Customer:

Color code: Dark Dolphin(PCM 450HQ 4282), Dove Grey(PCM 450HQ 4281), Fish Eagle White(PCM 450HQ 3755)

Contract No.:

- 1.The top paint coating will remain adherent to the steel base (excluding any minor peel-back at cut edges).
- 2.The top paint coating will provide an effective weatherproof membrane.
- 3.Chalking of top paint can perform as rating ≥ 2 according to ASTM D 4214-98.

LONGFA makes no guarantees, either express or implied beyond the facts hereof: including, without limitation, warranties of fitness for a specific application and merchantability and shall have no other liability with respect thereto.

This warranty shall be subject to the stipulations, limitations and conditions hereinafter set forth:

1. The paint shall be fabricated within 6 calendar months after shipment from LONGFA's manufacturing works.
2. The guarantee applies only to corrosion from the weather side and where more than 5% of the surface area of any one building is affected.
3. In the event of breach of this warranty, LONGFA shall have the option of replacing the defective paint or furnishing sufficient paint product to enable the Buyer to fabricate replacement panels for the defective panels, or by compensating Buyer with due regard to the pro-rata of actual performance versus warranted performance based on the selling price. No liability shall be accepted for any consequential loss or damages attributable to the failure.
4. LONGFA shall not in any event be liable for the cost of labor expended by others on any non-conforming sheet or for any special, indirect or consequential damages to anyone by reason of the fact that such panels shall have been non-conforming.
5. Claims must be promptly reported in writing to LONGFA and LONGFA shall be given a reasonable opportunity to inspect the panels claimed to be non-conforming. Adequate identification of the material involved in the claim, including but not limited to the date of painting, LONGFA order number, batch number, invoice number and date of shipment must be established and provided by the Buyer.
6. This warranty applies only to the paint coating that be applied to the panels..
7. Buyer shall exercise due diligence in inspection of coating as received from LONGFA so as to mitigate repair or replacement.
8. This warranty applies only on prime coil coating. The Buyer is advised to check for the LONGFA marking printed on the drums.
9. LONGFA extends this warranty solely to the Buyer. This warranty is non- transferable and non-assignable.
10. LONGFA reserves the right to terminate this warranty at any time (except as to orders already accepted) upon the giving of written notice thereof.
11. This warranty is intended by the parties to be a final, complete and exclusive statement of the agreement and is part of the contract for the purchase of coil coating and any and all previous verbal or written statements are hereby excluded.
12. This limited warranty shall be governed by and interpreted in accordance with the Law of China.

This warranty DOES NOT APPLY to sheets exposed at any time to corrosive or aggressive atmospheric conditions, including but not limited to :

- 1.Areas subject to salt-water marine atmosphere or to repeated spraying of either salt or fresh water.
- 2.Areas subject to fallout of or exposure to corrosive chemicals, ash, fumes, cement dust or animal waste.
- 3.Areas subject to water run-off from lead or copper flashing or areas in metallic contact with lead or copper.
- 4.Conditions or circumstances where corrosive fumes or condensates are generated or released inside the building.
- 5.Contact with soil, fertilizers or other moisture retaining substance.
- 6.Areas sheltered from periodic washing by natural rainfall or man-made fresh water rinse on a regular 6 monthly basic.

This warranty DOES NOT APPLY in the event of :

- 1.Mechanical, chemical or other damage sustained during shipment, storage, forming, fabrication, erection or during or after erection.
- 2.Forming which incorporates reverse bending or which subjects the coating to alternate compression and tension. Bends less than 2T for a sheet thickness of 0.40 mm and thinner and less than 3T for a sheet thickness over 0.40 mm.
- 3.Failure to remove debris form or provide free drainage of water, including internal condensation, from overlaps and all other surfaces of the sheets or panels.
- 4.Damage caused to the metallic coating by improper roll forming, scouring or cleaning procedures.
- 5.Deterioration of the panels caused by contact with green or wet lumber or wet storage stain caused by water damage or condensation.
- 6.Presence of damp insulation or other corrosive material in contact with or close proximity to the panel.
- 7.Deterioration to the panels caused directly or indirectly by panel contact with fasteners and sealants. (Suitable long-lasting fasteners and sealants should be selected by the Buyer.)
8. Slopes of the roof or of any section of the roof that is less than 10 degrees.
9. Severe marine, industrial or corrosive environments.
- 10.The temperature should keep in the range of 15~40 °C when forming; however, the finished prepainted steel sheet need not to be preserve constantly in the temperature higher than 80 °C.
- 11.Storm and tempest or other Acts of God and forcemajeure.